L Number	Hits	Search Text	DB	Time stamp
5	1	("5663750").PN.	USPAT	2004/05/27 16:06
6	14	5663750.URPN.	USPAT	2004/05/27 15:19
7	14	5663750.URPN.	USPAT	2004/05/27 15:20
8	7	("4908635" | "4970533" | "5132711" | "5136309" | "5160969" | "5414452" | "5576746").PN.	USPAT	2004/05/27 15:20
9	4	762145.ap.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/05/27 16:05
10	3	762145.ap.	USPAT	2004/05/27 16:06
11	1	("5530461").PN.	USPAT	2004/05/27 16:07
12	112	(print$3 near4 (attribute or parameter)) and brother$.as.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/05/27 16:08
13	38	((print$3 near4 (attribute or parameter)) and brother$.as.) and (ink adj3 jet)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/05/27 16:08
-	2	(("5387976") or ("5262797")).PN.	USPAT	2004/05/27 15:18
-	11	(monitor$3) with (print$3 near4 characterist$3 near4 operat$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/13 17:07
-	132	(monitor$3) with ((print$3 near4 characterist$3 near4 operat$3) or (print$2 adj2 mode))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/13 17:24
-	29	((monitor$3) with ((print$3 near4 characterist$3 near4 operat$3) or (print$2 adj2 mode))) and (real adj2 time)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/13 17:21
-	1	("6050666").PN.	USPAT	2003/11/13 17:17
-	3	6050666.URPN.	USPAT	2003/11/13 17:17
-	4	("4910528" | "5608439" | "5781205" | "5844583").PN.	USPAT	2003/11/13 17:18

-	0	5971582.URPN.	USPAT	2003/11/13 17:20
-	0	5971582.URPN.	USPAT	2003/11/13 17:20
-	1	"4261039".PN.	USPAT	2003/11/13 17:20
-	115	((monitor$3) with ((print$3 near4 characterist$3 near4 operat$3) or (print$2 adj2 mode))) and time	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/13 17:21
-	29	((monitor$3) with ((print$3 near4 characterist$3 near4 operat$3) or (print$2 adj2 mode))) and ((real adj2 time) or (real-time))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/13 17:22
-	251	(monitor$3) same ((print$3 near4 characterist$3 near4 operat$3) or (print$2 adj2 mode))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/13 17:24
-	39	((monitor$3) same ((print$3 near4 characterist$3 near4 operat$3) or (print$2 adj2 mode))) and ((real adj2 time) or (real-time))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/13 17:24
-	347	(compar$4) near10 (print$3) near10 (attribute or characteristic)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:52
-	701	(compar$4) near10 (print$3) near10 (attribute or characteristic)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:52
-	63125	(assign$4) near5 (weight or value or parameter)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:52
-	56	((compar$4) near10 (print$3) near10 (attribute or characteristic)) and ((assign$4) near5 (weight or value or parameter))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:52